Míele

Maxwell Adam



Miele

HM 16-80 [D]

Rotary ironer, electrically heated with steam function for optimum results and maximum convenience.



- Performance 13 % kg/h*, roller diameter 160 mm, working width 830 mm
- Iron comfortably while seated
- Work at your own pace thanks to variable roller speed
- Durable roller padding aramid needle felt cloth
- Easy to store fold-away function

EAN: 4002513471922 / Article number: 53168003GB / Material number: 06012090

| Construction type and design | | |
|--|---|--|
| Construction type | Laundry infeed and outfeed at the front | |
| Can be set up against a wall | • | |
| Range | Professional | |
| Outer casing | Lotus white | |
| Roller diameter in mm | 160 | |
| Working width in mm | 830 | |
| Heater plate material | Aluminium | |
| Padding | Polyester needle-felt cloth | |
| Ironer cover | ARAMID needle-felt cloth | |
| Application | | |
| Suitable for the hotel and catering industry | • | |
| Suitable for retirement and care homes | • | |
| Suitable for commercial laundries | • | |
| Suitable for offshore use | • | |
| Suitable for marine use | • | |
| Suitable for camp sites | • | |
| Performance data | | |
| Max. ironing performance at 20 % residual moisture in kg/h | 13 | |
| Tested operating hours | 2500 | |
| Controls | | |
| Control system | Rotary control | |
| Minimum ironing speed, controlled in m/min | 2 | |
| Maximum ironing speed, controlled in m/min | 4.5 | |
| Adjustable temperature | In temperature stages | |
| Standard electrical connection | | |
| Heating type | Electric | |
| Electrical connection | AC 220-240V 50-60HZ | |
| Electric heater rating in kW | 2.6-3.1 | |
| Boiler heater rating in kW | 0.85 | |
| Total connected load in kW | 2.7-3.2 | |
| Fuse rating in A | 13 | |
| Dimensions and weight | | |
| External dimensions, height in mm | 959 | |
| External dimensions, width in mm | 985 | |
| External dimensions, depth in mm | 380 | |
| External dimensions, gross height in mm | 570 | |
| External dimensions, gross width in mm | 1120 | |
| External dimensions, gross depth in mm | 450 | |
| Net weight in kg | 39 | |
| Gross weight in kg | 45 | |
| Maximum floor loading in N | 382 | |



HM 16-80 [D] Rotary ironer, electrically heated with steam function for optimum results and maximum convenience.



| Features | | |
|--|---|--|
| Steam function | • | |
| Free roller end | • | |
| Fold-away function | • | |
| Automatic finger guard | • | |
| Foot switch | • | |
| Airing bar | • | |
| 4 castors gentle on the floor | • | |
| Feed-in board | • | |
| Laundry return feed | • | |
| Option of ironing when seated | • | |
| Machine-independent accessories | • | |
| Test certificate | | |
| VDE | • | |
| CE | • | |
| WEEE | • | |
| VDE-EMC | • | |
| Complies with Machinery Directive 2006/42/EC | • | |



The Miele Company Limited Fairacres Marcham Road Abingdon OX14 1TW

Sales: 0845 365 6636

Customer Service: 0845 365 6608 miele-professional@miele.co.uk www.miele.co.uk/professional

Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment. For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.